

DESCRIPTION

Dimmer RF2,4GHz, 5-36Vdc, 8A*1CH, (24V/192W) c/push

FEATURES

TECHNICAL DATA

| | |
|-----------------------|---|
| Certifications | CE , RoHS , EMC , LVD |
| Regulations | ETSI EN 301 489-1 V2.2.3 ETSI EN 301 489 , EN 62368-1:2020+A11:2020 |
| Material | Metallo , Plastica |
| Packaging | Box |
| Attachment | Morsetto |
| Dimmable | SI |
| Connection | Collegamento in parallelo |
| Warranty | 5 years |
| IP grade | IP20 |

MODELLI

| Codice | Descrizione |
|------------|--|
| AMP-EV1-X | Amplificatore di segnale 1CH*30A 12-36Vdc |
| CTC-R11 | Telecomando RF 2,4Ghz dimmer 1 zona CR2032 |
| DMR-V1 | Dimmer RF2,4GHz, 5-36Vdc, 8A*1CH, (24V/192W) c/push |
| DMR-V1_R11 | Kit Centralina Dimmer push 12/24Vdc, 8A*1CH, (96/192W) c/radiocomando SI |
| DMR-V1_R6 | Kit Dimmer push 12/24Vdc, 8A*1CH, c/radiocomando |

SPECIFIC TECHNICAL DATA BY CODE

| | AMP-EV1-X | CTC-R11 | DMR-V1 | DMR-V1_R11 | DMR-V1_R6 |
|-----------------------|-------------------|----------|--------|------------|-----------|
| Current | 30A | | | | |
| Output voltage | 12,0/24,0/36,0Vdc | | | | |
| Input voltage | 12,0/24,0/36,0Vdc | | | | |
| Watt | 40,0/288,0W | | | | |
| Master BOX | | | | 30 | 30 |
| Inner BOX | 1 | 1 | 1 | 1 | 1 |
| Size | 107 x 75 | 139 x 36 | x 0 | x 0 | x 0 |